





# Contaminants Reduced:

- Chlorine Taste and Odor
- Sediment

## Residential/Commercial Filtration Applications

### **Standard Features**

- Manufactured in China
- Granular activated carbon (GAC) filter
- Two-stage water filter: first stage uses a graded density prefilter; second stage passes water through granular activated carbon to reduce unwanted tastes, odors and chlorine
- Compatible with Aqua-Pure® AP217; also fits Aqua-Pure® AP200 and Purwater® PW-200
- Manufactured with FDA CFR-21 compliant materials

## **Product Specifications**

#### **Filter Media**

Granular activated carbon (GAC)

#### **Micron Rating (Nominal)**

5 microns

#### **Chlorine Capacity**

2,000 gallons @ 2.0 GPM

#### **Dimensions**

3-3/8" OD x 7" (17.8 cm)

#### **Operating Temperature**

40°F to 145°F (4.4°C to 62.8°C)

#### **Maximum Flow Rate**

2 gpm

#### **Operating Pressure**

25 to 125 psi

#### **Change Frequency**

6 to 12 months

#### **WARNING:**

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



9450 SW Gemini Dr, ECM #83358, Beaverton, OR 97008 Tel 855.896.3525 · Fax 866.409.9622