NP-RFG10BB Radial Flow Filter Cartridge





Contaminants Reduced:

- Sediment, Dirt and Rust
- Chlorine Taste and Odor



This NP-RFG10BB filter is Tested and Certified by NSF International against NSF/ANSI Standard 42 for material requirements only.



Residential/Commercial Filtration Applications

Standard Features

- Manufactured in China
- Environmentally-friendly coconut shell granular activated carbon (GAC) filter
- for Ideal point-of-entry (POE) and other high flow rate application
- Compatible with Culligan® RFC-BBSA, Pentek® RFC-BB, Omnifilter® TO8, GE FXHTC, Aqua-Pure® AP817, American Plumber® WRC25HD, and Whirlpool® WHEF-WHPCBB
- Drop-in cartridge style
- Made with NSF 42 approved materials

Product Specifications

Filter Media

Coconut shell granular activated carbon (GAC)

Micron Rating (Nominal)

25 microns

Dimensions

4-1/2" dia. x 10"

Capacity

10,000 gallons

Operating Temperature

40 to 100°F (4.4 to 37.8°C)

Operating Pressure

30 to 100 psi

Maximum Flow Rate

3 gpm

Change Frequency

6 months

WARNING:

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.





9450 SW Gemini Dr, ECM #83358, Beaverton, OR 97008 Tel 855.896.3525 • Fax 866.409.9622

STUART, FL · BEAVERTON, OR · GREENVILLE, SC · SAN DIEGO, CA