

# Performance Data Sheet

## Model AP Easy CS-FF

Chemical Reduction Filter  
Use Replacement Cartridge C-CS-FF

This system has been tested according to NSF/ANSI Standard 42 for the reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system as specified in NSF/ANSI 42.



System tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of Chlorine Taste and Odor  
Capacity: 2,000 gal. (7,571 lit.) depending on local water conditions.

### Contaminant Reduction Determined by NSF Testing

Substance	Average Influent	Influent Challenge Concentration. Units apply to each row	Avg % Red.	NSF Reduction Requirements	Max. Effluent Concentration	Min. % Reduction	NSF Test Number
Chlorine taste and odor	2.0	2.0 mg/L $\pm$ 10%	78	$\geq$ 50%	0.89	59.5	5141775-04

Application Guidelines/Water Supply Parameters	
Service flow	2.0 gpm ( 7.57 lpm)
Water supply	Community or private well
Water pressure	40 - 125 psi (276 - 862 kPa)
Water temperature	40° F - 100° F (4.4° C - 38° C)

Note that while the testing was performed under standard laboratory conditions, actual performance may vary.

Systems must be installed and operated in accordance with manufacturer's recommended procedures and guidelines.

See Warranty Statement on front of Instruction Manual for details.

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

1/23/2006

Buyer \_\_\_\_\_ Seller \_\_\_\_\_

For estimated costs of replacement elements please call or visit our web site or

For service and parts contact Cuno Inc., a 3M company  
400 Research Parkway  
Meriden, CT 06450  
Toll Free: 1-800-222-7880  
World wide: 203-237-5541  
Fax: 203.238-8701  
www.aquapure.com - www.cuno.com

